





► Budynek Urzędu Miasta Stołecznego Warszawy



K719/3N

Nihil

surface mounted / recessed luminaire -
reflector and lens - rectangular - RAL9003-
white

housing of impact-resistant polycarbonate
escape route

self-test/communication: EST+ extensive self-
test

lumenoutput in emergency: 88 lm

Mechanical characteristics

dimensions: (LxWxH) 150 mm x 70 mm x 44
mm

weight: 0.7 kg

Optic

reflector and lens

Lamp

lamp type: LED - 1 x 3W

Battery


4 x NiMH 1,2V 1,25Ah

duration: 1 h

Electrical equipment

voltage: 220-230V AC

frequency: 50-60Hz




In m for 0.5 lux and 88 lm

h	a	b	c	d
2.8m	7.4	16.3	4.2	8.7
3.0m	7.7	17.2	4.1	9.0
3.5m	8.6	19.2	3.5	9.3
4.0m	9.3	21.1	3.4	10.0
4.5m	10.0	22.8	2.2	9.7
5.0m	1.7	19.4	1.0	9.2
5.5m	-	17.0	-	8.9
6.0m	-	15.7	-	7.5
6.5m	-	15.5	-	5.5
7.0m	-	5.5	-	3.0
7.5m	-	0.2	-	-
8.0m	-	-	-	-
8.5m	-	-	-	-
9.0m	-	-	-	-
9.5m	-	-	-	-

In m for 1 lux and 88 lm

h	a	b	c	d
2.8m	6.5	14.8	2.4	7.0
3.0m	6.9	15.4	2.0	6.9
3.5m	1.5	14.4	0.8	6.6
4.0m	-	11.6	-	6.1
4.5m	-	11.0	-	4.4
5.0m	-	3.4	-	1.7
5.5m	-	-	-	-
6.0m	-	-	-	-
6.5m	-	-	-	-
7.0m	-	-	-	-
7.5m	-	-	-	-
8.0m	-	-	-	-
8.5m	-	-	-	-
9.0m	-	-	-	-
9.5m	-	-	-	-



In m for 0.5 lux and 88 lm

h	a	b	c	d
1.5m	0.6	1.3	0.5	0.9
2.0m	-	-	0.5	1.0
2.5m	-	-	0.6	1.3
3.0m	-	-	0.7	1.4
3.5m	-	-	0.5	1.3
4.0m	-	-	-	-
4.5m	-	-	-	-
5.0m	-	-	-	-
5.5m	-	-	-	-
6.0m	-	-	-	-
6.5m	-	-	-	-

In m for 1 lux and 88 lm

h	a	b	c	d
1.5m	0.5	1.1	0.5	0.9
2.0m	-	-	0.5	1.0
2.5m	-	-	0.6	1.2
3.0m	-	-	0.6	1.3
3.5m	-	-	-	0.8
4.0m	-	-	-	-
4.5m	-	-	-	-
5.0m	-	-	-	-
5.5m	-	-	-	-
6.0m	-	-	-	-
6.5m	-	-	-	-

7.0m	-	-	-	-	7.0m	-	-	-	-
7.5m	-	-	-	-	7.5m	-	-	-	-
8.0m	-	-	-	-	8.0m	-	-	-	-
8.5m	-	-	-	-	8.5m	-	-	-	-

